

## 19-inch chassis 42U for cloud computing



## 19-inch chassis 42U for cloud computing



THE IT PRO'S CHOICE: Designed and built for IT Professionals, this 42U rack is backed for 2-years, including free lifetime 24/5 multi-lingual technical assistance



42U Server Rack Cabinet - 19" Network Rack Enclosure, 39" Deep Floor Standing Data Rack with Locking Glass Door, Cooling Fans, PDU & Shelf for Servers, Switches and Patch Panels



THE IT PRO'S CHOICE: Designed and built for IT Professionals, this 42U rack is ...



Up to 1% cash back · Lenovo Heavy Duty Rack Cabinets are industry-standard 19-inch 42U and 48U data center cabinets that are designed for high performance and high availability ...



Racks of 19" of high quality and finishes, made of high quality steel of 1.2mm ...



Racks of 19 "of high quality and finishes, made of high quality steel of 1.2mm thickness, painted in black color Rack cabinets with a system of very fast assembly and with very little hardware Professional ...



Compact width to optimize data center space. 42U height to easily roll through doorways. Includes: Baying hardware, Key (s), Keyed-alike doors and side panels, Leveling feet, Mounting hardware, Pre ...




Upgrade your data center with top 42U server rack cabinets like HP 42U G2 and Dell PowerEdge 4220. Maximize space efficiency. Buy now on eBay!



The CR1015 server rack is specifically designed to give a universal mounting platform for all standard-sized 19" rack mountable device. The CR1015 server rack is able to meet most major manufacturers" ...



Arion 42U 19 inch premium UL listed 3,000 lbs rates server cabinets are for all IT environments and data centers. Vendor neutral and supports all 19 inch standard equipment.



Each rack also comes with two sets of 19-inch EIA rails for sliding shelves, and the rack has split side panels with single locking slam latch that allows for easy single person installation and removal. Add ...



42U rack cabinet. Compatible with ANSI/EIA RS-310-D, IEC297-2, DIN41494, DIN41494, ETSI standard; 23.62 (W) x 39.37 (D) x 80.91 (H) inch. 71% ventilated rate of the high-density vented door. Heavy ...

## Contact Us

For more information, pricing, or custom energy solutions, please contact us:

Website: <https://www.gdroofing.co.za>

Email: [sales@gdroofing.co.za](mailto:sales@gdroofing.co.za)

Phone: +27 72 418 9365

Address: 22 Electron Avenue, Isando, Johannesburg, 1600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

