

GDR Telecom Site Energy Systems

Burkina Faso Transimpedance Amplifier QSFP-DD



Burkina Faso Transimpedance Amplifier QSFP-DD



This QSFP-DD dual pluggable EDFA booster amplifier offers a optical input range and provides a +20dB nominal gain to a C-Band DWDM link. The dual pluggable ...



Cisco QSFP-DD and OSFP 800G coherent optical modules are supported on Cisco switches and routers. For more details, refer to the Cisco Transceiver Modules Compatibility Matrix.



Our products are compatible with all major brands. This QSFP-DD dual pluggable EDFA booster amplifier offers a optical input range and provides a +20dB nominal gain to a C-Band DWDM link.



mechanical and thermal requirements of the pluggable QSFP Double Density (QSFP-DD/QSFP-DD800) and the QSFP112 module in the classic 4-lanes QSFP form factor, connector and cage system.



The FJS1000 quad 64GBd Linear Mach-Zehnder modulator driver with 4VP-P output and 1.95W typical power dissipation enables QSFP-DD and OSFP form factor silicon photonics optical transceivers.



July 11, 2019 - QSFP-DD Hardware Specification
for QSFP DOUBLE DENSITY 8X PLUGGABLE
TRANSCIVER - Rev 5.0 May 8, 2019 - Common
Management Interface Specification - Rev 4.0

Contact Us

For more information, pricing, or custom energy solutions, please contact us:

Website: <https://www.gdroofing.co.za>

Email: sales@gdroofing.co.za

Phone: +27 72 418 9365

Address: 22 Electron Avenue, Isando, Johannesburg, 1600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

