

# Calculation Table for Metal Cable Tray Supports



## Overview

EzyCalculator is an interactive online tool designed to help you calculate safe loads to spans for steel, aluminium and FRP strut and cable support components. Cable tray is a structural support system that carries cables and conductors while leaving them accessible for inspection, heat dissipation, maintenance, and future changes. Tray cable is a listed cable type, often marked TC or TC-ER, designed for installation in cable tray under its listing and. Cable tray support quantity can be calculated using a simple formula: Support Quantity = Total Length ÷ Support Spacing + 1  $20 \div 2 + 1 = 11$  supports In a typical project, a 20-meter cable tray with 2-meter spacing requires 11 supports. the Maximum Allowable Load is 0kg. Sum Area (in<sup>2</sup>) Comments Maximum allowable tray fill per Area (in<sup>2</sup>) Tray Design Depth = Sum of OD (in) Total Cross Sectional Areas of all cables: Total Sum of the Diameters: in. Per NEC Tray Sizing Instructions 1) Insure that macros have been enabled. Follow these steps to generate your accurate Bill of Materials (BOM) and engineering report: Step 1: Define.


## Calculation Table for Metal Cable Tray Supports



The right cable tray sizing calculator helps engineers turn cable schedules into a verified tray width and fill check before material ordering and site installation.



Easily calculate cable tray load capacity, verify NEC fill ratios, and generate a complete Bill of Materials (BOM) instantly. Free engineering tool by Shielden.



The document provides specifications for cable tray and cable weights, support spacing, and live load factors. It includes calculations for total load per meter, load per support, and load per threaded rod, ...



Learn how to accurately calculate cable tray support quantities in electrical installation projects. Our guide covers methods, tools, and practical examples for effective cable tray support ...



7) Once the calculate button has been selected, the program will take you to the output page, where the tray size needed will be displayed, as well as the article of the NEC that it falls under.



EzyCalculator is an interactive online tool designed to help you calculate safe loads to spans for steel, aluminium and FRP strut and cable support components.



Calculate cable tray fill per NEC 392 — ladder, solid-bottom, and ventilated trough trays with sizing examples and code requirements.



Cable tray is a structural support system that carries cables and conductors while leaving them accessible for inspection, heat dissipation, maintenance, and future changes.



The the following sections of this page tables and formulas are provided to help determine how many cables can be safely carried by each size wire mesh / cable tray.



With a support span of 20" and a total working load of 80 lbs/ft, a NEMA Class 20B tray rated at 75 lbs/ft will not be adequate. A NEMA Class 20C tray, rated at 100 lbs/ft, will be required.

## Contact Us

For more information, pricing, or custom energy solutions, please contact us:

Website: <https://www.gdroofing.co.za>

Email: [sales@gdroofing.co.za](mailto:sales@gdroofing.co.za)

Phone: +27 72 418 9365

Address: 22 Electron Avenue, Isando, Johannesburg, 1600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

