

Core Switch NQA Authorization



Overview

This document provides the use precautions of the product, including licenses, software versions, feature dependencies, limitation, and involved network elements. As shown in Figure 1, configure an NQA ICMP echo operation to test the roundtrip time between Device A and Device D through Device B. Nothing herein should be construed as constituting an additional warranty.) Do as follows on. A global ICT bridge delivering authentic hardware and trusted service for over 20 years. If the number of running test instances reaches the.



Core Switch NQA Authorization



Consistent with FAR 12.211 and 12.212, Commercial Computer Software, Computer Software Documentation, and Technical Data for Commercial Items are licensed to the U.S. Government ...



When you configure an NQA UDP tracert operation, follow these restrictions and guidelines: · Make sure the devices can reach each other before you start the NQA operation.




This chapter describes how to configure the Network Quality Analysis (NQA) to monitor the network operating status and collect network operation indexes in real time.




To configure the ICMP test, you need between the NQA client and the device under test is reachable. (ICMP test has a similar function with the ping command, but the output is more detailed.)



The NQA server makes a response to the request originated by the NQA client by listening to the specified destination address and port number. Follow these steps to configure the NQA server:



As shown in Figure 14, on Switch A configure a static route to Switch C, with Switch B as the next hop. Associate the static route, track entry, and NQA test group to verify whether static route is active in ...



The Huawei NQA Function License EH1SNQA00000 is designed specifically for the S9700 series, enhancing its network quality analysis capabilities. This license enables advanced monitoring and ...



NQA Configuration Commands Command Support Commands provided in this section and all the parameters in the commands are supported by all switch models by default, unless otherwise ...



The NQA operations for services that are already provided by the destination device such as FTP do not need the NQA server. You can configure the NQA server to listen and respond to specific IP ...

Contact Us

For more information, pricing, or custom energy solutions, please contact us:

Website: <https://www.gdroofing.co.za>

Email: sales@gdroofing.co.za

Phone: +27 72 418 9365

Address: 22 Electron Avenue, Isando, Johannesburg, 1600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

