

## Fiber optic cable



## Fiber optic cable



As optical passive devices, FS attenuators are mainly used in fiber optic to debug optical power performance & optical instrument calibration correction & fiber signal attenuation to ensure the optical ...



Fibertronics, Inc.'s in-line fixed cable attenuator is built to meet your low reflection attenuation requirements. Each cable assembly is custom built to meet your needs. We provide up to 10 meters ...



These versatile in-line attenuators are the perfect solution for attenuating ...



The fiber optic cable features a 10dB attenuation for efficient signal transmission over long distances. The cable supports OS1 single-mode fiber for high-speed data transfer and minimal signal loss.




This male-to-female LC/UPC attenuator has an attenuation value of 10 dB and is well suited for fiber amplifier, DWDM and telecommunications equipment. It features high optical power endurance and ...



LC/UPC M-F Fixed Singlemode Attenuator 5DB, 10DB, 15DB and 20D. Attenuator ...



LC/UPC M-F Fixed Singlemode Attenuator 5DB, 10DB, 15DB and 20D. Attenuator ensures low bit error rates preventing damage to receiving fiber optic equipment.



This Fiber Optic Attenuator, Fixed - SC/UPC 10dB is necessary to prevent over saturating an optical receiver when the optical power is too high. Using attenuators will ensure low bit error rates and ...



Fiber Optic Cable Types Fiber optic cable is designed to transmit data using light signals instead of electricity, making it faster, more secure, and immune to electromagnetic interference compared to ...



These versatile in-line attenuators are the perfect solution for attenuating Singlemode fiber connectors for both lab and commercial applications. Constructed of the highest quality materials and factory ...



Low Insert-loss & High Return-loss: Optical fibers are connected by adapters through internal open sleeves. Provide LC adapters to ensure the connection between fiber patch cable.



The FLA-SCUSM-10D from ShowMeCables features SC connectors and 9/125 single mode fiber with an attenuation level of 10dB, which allows for directly connecting transmitter and receiver ports (looping ...

## Contact Us

For more information, pricing, or custom energy solutions, please contact us:

Website: <https://www.gdroofing.co.za>

Email: [sales@gdroofing.co.za](mailto:sales@gdroofing.co.za)

Phone: +27 72 418 9365

Address: 22 Electron Avenue, Isando, Johannesburg, 1600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

