

Fiberboard Residue



Overview

The wood-based panel industry is experiencing an excessive accumulation of solid residues from the production of medium-density fiberboard (MDF) panels and moldings. It is possible to create new MDF products with acceptable physical and mechanical properties by revaluing MDF residues. Additionally, the potential of using residual softwood fibers from the pulp and paper industry for producing eco-friendly, zero-formaldehyde fiberboard panels, bonded with calcium lignosulfonate (CLS) as a lignin-based, formaldehyde free adhesive, was investigated in this work. After single-factor optimization, the central levels of bran, molasses, and magnesium sulfate were obtained. This study develops the LCI data for. Medium density fibreboard production by hot pressing without adhesive using *Triarrhena sacchariflora* residue bio-pretreated by white-rot fungus *Coriolus versicolor*

Correspondence Jianguo G. Wu, Jiangsu Key Laboratory for Eco-Agricultural Biotechnology around Hongze Lake, Jiangsu Key Laboratory for.


Fiberboard Residue



This study aims to develop a wood-based fiberboard made of MDF residues, capable of storing thermal energy.



This study aims to create a new type of fiberboard that is made entirely from MDF residues and can store thermal energy since it contains PCM while meeting the ANSI standard ...



During the pretreatment of poplar fiber by *T. hirsuta* LX1, laccase and sugar were produced, which played a crucial role in the non-adhesive adhesion of fiberboard.



They mainly come from logging residues, such as small diameter wood and branches, as well as wood resource processing residues, such as shavings and sawdust. Therefore, fiberboard can fully utilize ...



Recycling medium-density fibreboard (MDF) enhances material efficiency and contributes to waste management. This study investigates the impact of secondary fibres, generated from ...



LCA reports break down the cradle-to-gate results according to PCR standards for resource extraction, including residue production, transportation, and onsite WCP production.




The potential of using residual softwood fibers from the pulp and paper industry for producing eco-friendly, zero-formaldehyde fiberboard panels, bonded with calcium lignosulfonate (CLS) as a lignin ...



To produce fibreboard with *Triarrhena sacchariflora* residue (TS R) without adhesive and understand the relationship between bio-pretreatment and mechanical property of fibreboard.



Various aspects of binderless fiberboard manufacturing such as raw material suitability, effects of pretreatments and manufacturing process on physical, mechanical and thermal properties ...



This study develops the LCI data for medium-density fiberboard (MDF), a composite wood panel product comprised of wood fibers, urea-formaldehyde resin, wax, and other additives.

Contact Us

For more information, pricing, or custom energy solutions, please contact us:

Website: <https://www.gdroofing.co.za>

Email: sales@gdroofing.co.za

Phone: +27 72 418 9365

Address: 22 Electron Avenue, Isando, Johannesburg, 1600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

