


Four-port information panel remote monitoring type



Four-port information panel remote monitoring type



NL4 is a four data port network module that communicates and controls power status over a local or wide area network. The NL4 provides four SPI ports for connection to FlexPower devices that ...



EOL monitoring with single or double termination on all REX, contact and auxiliary inputs supported with user-installed 1K resistors. Extend your system to connect more entries and devices by adding ...



In order for the dialer to be able to seize the phone line to report an alarm or other event when other customer equipment (telephone, answering system, computer modem, etc.) connected to the same ...




The CM1284 allows for connection of up to 4 HDMI computers and 2 HDMI displays, facilitating real-time monitoring of multiple video sources on a single multi-view display with up to 4K DCI visual quality.



DeviceMaster® RTS 4-Port DB9 serial communications devices. When used with the included NS-Link™ driver software and a host PC, the DeviceMaster RTS enables placement of COM or TTY ports ...



NL4 is a four data port network module that communicates and controls power status over a local or wide area network. The NL4 provides four SPI ports for connection to FlexPower devices that ...



NL4 is a four data port that communicates and controls power status over a local or wide area network. The NL4 provides four SPI ports for connection to FlexPower devices that enables monitoring and ...



Type I CAs are intended for workstation environments that are used to view and process compartmented information. These areas may be comprised of open bays, open spaces, or a set of ...



The EC1000 Energy Box has four Energy Sensor ports to connect to four Energy PDU modules and four Environment Sensor ports for external sensors to monitor environmental conditions.



The EC1000 Energy Box has four Energy Sensor ports to connect to four Energy ...



NL4 is a four data port network module that communicates and controls power status over a local or wide area network. The NL4 provides four SPI ports for connection to FlexPower devices that ...

Contact Us

For more information, pricing, or custom energy solutions, please contact us:

Website: <https://www.gdroofing.co.za>

Email: sales@gdroofing.co.za

Phone: +27 72 418 9365

Address: 22 Electron Avenue, Isando, Johannesburg, 1600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

