

Gulf Region Optical Amplifier 40G



Gulf Region Optical Amplifier 40G



The DSC-R411 is a high-gain PIN + Transimpedance + Limiting amplifier ideally suited for both singlemode & multimode digital applications up to 43 Gb/s. The ...



It amplifies tiny high-speed signal levels to a higher level than driving the modulator. It goes niobium Lithium (LiNbO3) electro-optical modulator work, and having in the broadband range has a better ...



The 40G IQ optical transmitter module comprises Ti \square LiNbO3 QPSK Dual-Drive Mach-Zehnder modulator, Dual Input 28Gb/s Broadband 8V Lithium Niobate Modulator Driver amplifier and bias ...



The KG-RF-40 Broadband Microwave Amplifier is a benchtop instrument specifically designed for high-speed lithium niobate electro-optic modulators, and it amplifies tiny high-speed signal levels to a ...



The 40G transceiver module portfolio offers customers 40Gigabit Ethernet connectivity options for data center, high-performance computing networks, enterprise core and distribution layers, and service ...



The Optilab PR-40G-M is a high speed photo receiver module. Featuring 30 GHz bandwidth and 3000 V/W differential conversion gain, this module can be used in digital application as high as 40 Gbps.



The DSC-R411 is a high-gain PIN + Transimpedance + Limiting amplifier ideally suited for both singlemode & multimode digital applications up to 43 Gb/s. The R411 is available in two GPPO ...



Broadex Technologies' high performance and cost effective 40G Optical Transceiver Modules are built utilizing our innovative COB technology. These reliable and robust QSFP+ modules support high ...



FS 40G QSFP+ optical transceiver module solutions offer a full range of QSFP+ modules from 150m to 80km reach, and used for high-density switching, routing and data center applications.



The Alcatel QSFP-40G-SR is a high-performance 40GBase-SR4 optical transceiver designed for data centers and enterprise networks. Operating at an 850 nm wavelength, it delivers reliable data ...



Today, our 40 Gb product line has evolved to include PIN+TIA optical receivers, with both linear and limiting amplifiers. These receivers work up to 40 Gb from 1064 nm to 1650 nm for single mode ...

Contact Us

For more information, pricing, or custom energy solutions, please contact us:

Website: <https://www.gdroofing.co.za>

Email: sales@gdroofing.co.za

Phone: +27 72 418 9365

Address: 22 Electron Avenue, Isando, Johannesburg, 1600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

