

# High-voltage distribution box number code



## Overview

Typical code letters include Q for circuit breakers, T for transformers, A for assemblies (switchboards), etc. There are specified in more detail in IEC 60617 for each type of device. Generally we number each product in a logical fashion which fits the project (i. -Q1, -Q2 . This standard describes requirements for numbering and labeling of real property electrical distribution equipment, circuits, and site lighting at Lawrence Livermore National Laboratory. This is an internal LLNL standard meant to guide the design of new facilities, facility modifications, and. As the largest independent specification firm they are knowledgeable about both the needs of specifiers and architects and how to support manufacturers in their marketing to design professionals Announcement Electrical Generating Systems Assoc. - On-site power generation National Fire Protection. Purpose - This Article is about all electrical equipment numbering system, Electrical Panel Numbering System, Electrical Wire Numbering System, Electrical Relay Numbering System, Electrical Drawing Numbering System, Electrical Schematic Numbering System, Electrical Cable Numbering Systems. This code is part of the latest version of Uniclass. 42, April 2026 Still need help?

Browse the full set of Uniclass tables, delivered, managed and maintained by NBS. In electric power systems and industrial automation, ANSI Device Numbers can be used to identify equipment and devices in a system such as relays, circuit breakers, or instruments.

## High-voltage distribution box number code



The relay logic will monitor the current as well as breaker status and if the breaker fails to operate after the time expires, relay will trip and lockout all the other 34.5kV circuit breakers as well as the high ...




Each panelboard is considered a main and takes the number switchgear appended by the feeder number and a sequential letter (e.g., A, B, C); in this case, 65A1A and 65A1B.



When one device performs several protective functions, it is typically denoted "11" by the standard as a "Multifunction Device", but ANSI Device Numbers are still used in documentation like single-line ...



This code is part of the latest version of Uniclass. Products v1.42, April 2026. Still need help? Browse the full set of Uniclass tables, delivered, managed and maintained by NBS.



This engineering article defines the numbering system used for the design of low voltage (LV) (i.e., below 690 Volts a.c.) and high voltage (HV) (i.e., up to 150 kV a.c.) installations.



Boards, cabinets and similar combinations of apparatus for electric control or the distribution of electricity, for a voltage  $> 1.000 \text{ V}$  but  $\leq 72,5 \text{ kV}$



ANSI Standard Device Numbers & Common Acronyms  
ANSI Standard Device Numbers & Common Acronyms



View the TI High-voltage power distribution box block diagram, product recommendations, reference designs and start designing.



Free architectural library for electrical, lighting and power distribution design information, quickly access manufacturer's websites for the product information you need.



If the expected operating voltage is greater than the value given below, the clearances in this bulletin may be inadequate. Refer to the 2012 edition of the NESC for guidance.

## Contact Us

For more information, pricing, or custom energy solutions, please contact us:

Website: <https://www.gdroofing.co.za>

Email: [sales@gdroofing.co.za](mailto:sales@gdroofing.co.za)

Phone: +27 72 418 9365

Address: 22 Electron Avenue, Isando, Johannesburg, 1600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

