


Hot-swappable power distribution unit anti-tracking shipped worldwide



Hot-swappable power distribution unit anti-tracking shipped worldwide



Each PDM consists of an industry standard circuit breaker, branch current monitoring (BCM), output cable and connector plug combined into a hot-swappable module that feeds power to IT racks.



We keep moving forward learning the world experience in the IT field and needs of our customers, trying to improve and bring our solutions to the level of world IT leaders and even surpassing in some ...



Each PDM consists of an industry standard circuit breaker, branch current monitoring (BCM), output cable and connector plug combined into a hot-swappable module that feeds power to IT racks.



Facilitates hot-swappable battery replacement from the front panel—with no need to remove the UPS from the rack—the HotSwap MBP is also ideal when exchanging a faulty unit or upgrading to a new ...



This hot-swappable digital outputs expansion module provides 16 potential free contact outputs to issue substation automation control commands. Hot-swappable electronics include millisecond ...



Hot Swap MBPs enable easy UPS replacement without interruption to the connected load. Placing the HotSwap MBP in bypass mode provides utility power to equipment while the UPS is being serviced.



The TCD-HS SERIES Hot Swap Power Supply is available in a ruggedized “COTS” version for military applications. Custom configurations and other voltages and power levels are available.



Optimize industrial power systems with hot-swap controllers that enable safe live insertion and removal of boards without disrupting operation. They manage inrush current, protect against electrical faults, ...



Feature highlights: This intelligent PDU features hot-swappable electrical metering, anti-loose sliders, and RS485 communication for efficient rack-mounted power distribution.



SmartOnline hot-swappable modular UPS systems feature a modular power distribution unit (PDU) that combines all input and output power connections with a manual bypass switch.

Contact Us

For more information, pricing, or custom energy solutions, please contact us:

Website: <https://www.gdroofing.co.za>

Email: sales@gdroofing.co.za

Phone: +27 72 418 9365

Address: 22 Electron Avenue, Isando, Johannesburg, 1600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

