

# How to calculate the number of optical modules needed



## Overview

The number of spine switches required is calculated by dividing the number of cables by the number of leaf switches, which results in the need for  $(8 \times \text{SU} \times 200) / (8 \times \text{SU})$  spine switches. GPUs such as the A100, H100, and upcoming GH100 require high-speed optical interconnects to link thousands of GPU nodes, enabling large-scale AI model training and inference.



## How to calculate the number of optical modules needed




Read the definitive 2026 guide on SFP modules. We explain Single Mode vs Multimode, DDM diagnostics, and how to choose the right transceiver for Cisco, Juniper, and more.



In the market, there are different versions of the ratio of optical transceivers to the number of GPUs, and the figures of various versions are not consistent mainly because the amount of optical ...



There are multiple methods on the market for calculating the ratio between compute optical modules and GPUs, resulting in different outcomes. The main cause of these differences is ...



This article discusses how different architectures and components in high-performance computing (HPC) networks affect the number of optical modules required for GPUs.



Explore the factors influencing the number of optical modules required for GPUs in various networking architectures. Learn about different network card and switch models, the scalable unit ...



## Contact Us

For more information, pricing, or custom energy solutions, please contact us:

Website: <https://www.gdroofing.co.za>

Email: [sales@gdroofing.co.za](mailto:sales@gdroofing.co.za)

Phone: +27 72 418 9365

Address: 22 Electron Avenue, Isando, Johannesburg, 1600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

