


Libyan CIF price 1 6T optical module 200G



Overview

6T-DR8 OSFP224 LPO transceiver offers 8 channels of 200G-PAM4, 500m reach, and supports IEEE 802. 6T Ethernet networks - AscentOptics. Current price is: \$4,950. It supports up to 500m reach over single-mode fiber, operates within a 0°C-70°C case temperature range, and complies with. Amphenol's 200G/lane optical modules support DR4, FR4, 2×DR4, 2×FR4, AOC, and breakout AOC configurations with LC or MPO ports, ideal for 800G/1. Fully compliant with OSFP MSA, IEEE 802. 3, and OIF-CMIS standards, and RoHS compliant per EU directives 2011/65 and 2015/863. The MTRO-D5F8CL is designed to operate in switch and router applications supporting OSFP MSA compliant traffic for up to 500m links.

Libyan CIF price 1 6T optical module 200G



1.6T-DR8 OSFP224 LPO transceiver offers 8 channels of 200G-PAM4, 500m reach, and supports IEEE 802.3df, ideal for 1.6T Ethernet networks - AscentOptics.



The MTRO-D5F8CL is designed to operate in switch and router applications supporting OSFP MSA compliant traffic for up to 500m links.



NADDOD offers 1.6T/800G InfiniBand XDR solutions, which combine transceivers with cables. The transceiver portfolio includes 1.6T 2xDR4 and 2xFR4 OSFP224 transceivers in IHS and RHS ...



The module features 8 independent transmit and receive channels, each operating at 200Gb/s, supporting a total data transmission rate of up to 1.6Tb/s over single ...



Current price is: \$2,800.00. Add to cart.
Eoptitech's 800G OSFP / 800G QSFP-DD and 1.6T OSFP224 Hybrid ACC+ copper cable products leverage a key...



Amphenol's 1.6T OSFP transceiver delivers 200G per lane to support advanced 800G and 1.6T Ethernet applications, enabling high-speed, high ...




200G/400G/800G optical module features up to 40km transmission distances using QSFP56/QSFP-DD footprints for data center interconnect applications - FiberMall



Broadcom's Active Copper PHY portfolio enables DAC cable providers to build very low insertion-loss profile, ultra-low latency, ultra-low power cables for 100G/400G/800G/1.6T hyperscale/AI networks ...



Sate Optics offers 1.6T OSFP optical transceiver modules with 8x200G architecture, EML & silicon photonics options, compliant with IEEE802.3dj and OSFP MSA. Ideal for 1.6T Ethernet, AI/ML ...



1.6T-DR8 OSFP224 based on 8 channels of 200G-PAM4 electrical and optical parallel lanes, 500m maximum reach via single mode fiber, case temperature ...

Contact Us

For more information, pricing, or custom energy solutions, please contact us:

Website: <https://www.gdroofing.co.za>

Email: sales@gdroofing.co.za

Phone: +27 72 418 9365

Address: 22 Electron Avenue, Isando, Johannesburg, 1600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

