

## Om3 Armored Tail Fiber Optic Agent



## Om3 Armored Tail Fiber Optic Agent




These multifiber cables use individually jacketed 900 μm buffered fibers enabling easy, consistent stripping and facilitating termination. The fibers are grouped into jacketed subunits and surrounded ...



... provide a smaller crush resistant pathway for improved design flexibility and lower installed cost. This cable is available with OS2 Singlemode, OM1 Multimode, or the highest quality OM3 and OM4 laser ...



Browse our armored fiber optic cables and patch cables today. We carry OM4 and OM3 fiber optical jumpers, 50/125 10G, 40G, 100G, LSZH rated and more.



This armored cable consists of 0.9mm tight buffered fiber surrounded by an Aramid yarn (similar to Kevlar®) strength member. The core is protected by a spiral-wrapped steel tube that offers an easy ...



The armored fiber patch cable with built-in metal armor can resist mechanical damage from crushing, abrasion, cutting, and pulling in the most hazardous areas. It can protect fibers and prevent network ...



These multifiber cables use individually jacketed 900  $\mu\text{m}$  buffered fibers enabling ...



This 12 fiber indoor armored cable is OM3, Plenum (OFNP) rated and features 900um buffered fibers. When you order products from Anixter , the order is processed within one to two business days. ...



Armored cables are designed for improved mechanical and rodent protection in direct bury applications. The rugged loose tube design offers reliable transmission performance over a broad temperature ...



Fiber cable assembly, OSP armored, multimode (OM3), loose tube, 2mm - 36" breakout, LC, LC, simplex, built to specified length, with pulling sheath.



OM3 armored fiber optic patch cable for data centers and LANs. High-speed 10Gbps, versatile LC/SC/FC/ST connectors, durable 3.0mm jacket for harsh environments.



This high-quality multimode fiber optic patch cable is designed for ethernet applications. Each connection has great durability and is resistant to pulls, strains, and impacts during installation.

## Contact Us

For more information, pricing, or custom energy solutions, please contact us:

Website: <https://www.gdroofing.co.za>

Email: [sales@gdroofing.co.za](mailto:sales@gdroofing.co.za)

Phone: +27 72 418 9365

Address: 22 Electron Avenue, Isando, Johannesburg, 1600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

