


# GDR Telecom Site Energy Systems

## PRS30 optical module



## PRS30 optical module




Description: Pro-Spray PRS30 Sprinkler Body, 10 cm pop-up with 2.1 bar; 210 kPa bar pressure regulator, check valve, 1/2" inlet, and brown cap; accepts female thread nozzles



PROS-06-SI-PRS30 = 6" Pop-up with side inlet regulated at 30 PSI  
PROS-06-PRS30-CV = 6" Pop-up regulated at 30 PSI, drain check valve  
PROS-12-PRS30-CV-F-R = 12" Pop-up regulated at 30 PSI, ...



Engineered with a 30 PSI pressure regulator it provides consistent spray output across every nozzle reducing water waste and improving zone uniformity. This sprinkler body supports WaterSense ...




The brown-capped PRS30 takes all the rugged and reliable features of the Pro-Spray body and delivers efficient pressure regulation by keeping water pressure at a constant 30 PSI.



© 2026 - Ewing Irrigation Products, Inc. All Rights Reserved.



What does "PRS30" mean, and why does pressure regulation matter? PRS stands for Pressure Regulating Spray. The "30" refers to the outlet pressure the built-in regulator maintains — ...



The brown-capped PRS30 regulates the water pressure to a constant 30 PSI for the most efficient operation. A 10 PSI pressure differential is required to activate the 30 PSI regulator.



The brown-capped Pro-Spray PRS30 takes all the rugged and reliable features of the Pro-Spray and delivers efficient pressure regulation by keeping water pressure at a constant 30 PSI.



The built-in regulator holds pressure at 30 PSI (2.1 bar / 210 kPa) to optimize nozzle operation, reduce misting, and minimize water waste. Available in shrub, 4", 6", and 12" pop-up heights, the PRS30 ...



The Pro-Spray PRS30 optimises performance from the Pro Adjustable and Pro Fixed Nozzles, and is available in shrub, 7.5 cm, 10 cm, 15 cm, and 30 cm pop-up heights. It is recommended for both ...

## Contact Us

For more information, pricing, or custom energy solutions, please contact us:

Website: <https://www.gdroofing.co.za>

Email: [sales@gdroofing.co.za](mailto:sales@gdroofing.co.za)

Phone: +27 72 418 9365

Address: 22 Electron Avenue, Isando, Johannesburg, 1600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

