

Standard optical cable Gyts 48 cores





Overview


PBT loose tube of 2-12 fiber, Tube thickness: 0.3 ± 0.05 mm, Diameter: 2.1 ± 0.1 um, Fiber (Fiber characteristic), Cladding diameter: 125.0 ± 0 , Fiber characteristics: Diameter: 242 ± 7 um, UV color fiber: Standard ch.





Standard optical cable Gyts 48 cores

	<p>Length of cable: generally is 2KM/Drum, can be customized. Cable printing: standard printing or can be customized. Other requirement: can be negotiated. Cable marking The cable sheath shall be marked ...</p>
---	--

	<p>Durable 48 core GYTS53 fiber optic cable with steel tape armor, waterproof design, and UV-resistant PE jacket for underground/duct installation.</p>
---	---

	<p>Structure and Technical Specifications.</p>
--	--

	<p>The GYTS Fiber Optical Cable consists of optical fibers placed in a central loose tube, with fillers stranded around a metallic central strength member. The cable is then twisted using an SZ pattern ...</p>
---	---

	<p>Features Up to 288 fibers. Loose tube gel-filled construction for superior fiber protection. Corrugated steel tape armor to protect cable from mechanical damage and rodent protection. UV and moisture ...</p>
---	--



Outdoor Fiber Optic Cable, 48 Core, Steel Armored, PE, Jelly filled, GYTS, Single Mode OS2 9/125 (G652D) 10.6mm



48 Core GYTS Fiber Optic Cable Stranded Steel Tape Cable is the outdoor fiber optic cable type used for duct and aerial applications. We supply single mode GYTS fiber optical cable and multimode ...



Explore the details, specifications and video of our GYTS Fiber Optic Cable 48 Core, and order high-quality GYTS Fiber Optic Cable 48 Core from our factory directly at competitive pricing.



48-Cores GYTS Fiber Optic Cable from MeFiberOptic is designed for outdoor telecommunication and backbone networks. It is a loose-tube cable with steel tape armor, providing excellent mechanical ...



Durable 48-core GYTS fiber optic cable with steel tape armor, G652D single-mode fiber, and PE sheath. Ideal for outdoor telecom, FTTH, and harsh environments. 25-year warranty.

Contact Us

For more information, pricing, or custom energy solutions, please contact us:

Website: <https://www.gdroofing.co.za>

Email: sales@gdroofing.co.za

Phone: +27 72 418 9365

Address: 22 Electron Avenue, Isando, Johannesburg, 1600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

